



### GANTRAIL 3120/15/35 Clip

- 1 Rail
- 2 Gantrail MKII pad
- 3 Gantrail 3120/15/35 clip
- 4 Epoxy or cementitious grout
- 5 Steel sole plate
- 6 Nut and soft washer for levelling
- 7 M20 hold down bolt
- 8 Bolt grout

Rail	Origin	A mm	F mm	C mm	Kg/m	B mm	D mm	E mm	W mm	V mm	I mm	J mm	K mm
BS113A	U.K.	159	140	70	56.8	166	15*	**	300	121	214	110	***
S41	GERMANY	138	125	67	41	145	15*	**	275	100	199	110	***
S49	GERMANY	149	125	67	49.4	156	15*	**	275	111	199	110	***
60kg	AUSTRALIA	170	146	70	61	177	15*	**	300	132	220	110	***
UIC60	EUROPE	172	150	74	60.3	179	15*	**	300	134	224	110	***
ISCORS57	SOUTH AFRICA	165	140	70	57.4	172	15*	**	300	127	214	110	***
104lb CR	U.S.A.	127	127	64	51.6	134	15*	**	275	89	201	110	***

\* 15mm typical - Gantrail can advise for specific applications

\*\* Dimension 'E' is determined by the application and the type of grout used.

\*\*\* Dimension 'K' is usually between 600mm and 900mm for most applications. This dimension varies depending on factors such as wheel load and usage. Gantry Railing can provide calculations to determine this dimension subject to availability of critical data.

**Note:** Rails listed are those most commonly used with the 3120/15/35 clip. For compatibility with other rails, inquiries should be made direct to Gantry Railing Limited

## GANTRY RAILING LIMITED

International crane rail mounting specialists

NOT FOR DISTRIBUTION IN NORTH AMERICA AND CANADA



GANTRAIL®