



GANTRAIL 3120/15/35 Clip

- 1 Rail
- 2 Gantrail MKII pad
- 3 Gantrail 3120/15/40 clip
- 4 Epoxy or cementitious grout
- 5 Steel sole plate
- 6 Nut and soft washer for levelling
- 7 M20 hold down bolt
- 8 Bolt grout

Rail	Origin	A mm	F mm	C mm	Kg/m	B mm	D mm	E mm	W mm	V mm	I mm	J mm	K mm
ISCOR 40	SOUTH AFRICA	127	127	63.5	40.31	134	15*	**	275	84	201	110	***
46 AFNOR	FRANCE	146	134	64.5	46.36	153	15*	**	300	103	208	110	***
ISCR 80	INDIA	130	130	87	64.2	137	15*	**	300	87	204	110	***
135 CR	U.S.A	146	132	87	66.97	153	15*	**	300	103	206	110	***
50kg/m BR	U.K.	76	165	59	50.2	83	15*	**	320	33	239	110	***
BS113A	U.K.	158.7	139.7	69.9	56.8	165.7	15*	**	300	115.7	213.7	110	***
UIC 60	EUROPE	172	150	74	60.3	179	15*	**	300	129	224	110	***

* 15mm typical - Gantrail can advise for specific applications

** Dimension 'E' is determined by the application and the type of grout used.

*** Dimension 'K' is usually between 600mm and 900mm for most applications. This dimension varies depending on factors such as wheel load and usage. Gantry Railing can provide calculations to determine this dimension subject to availability of critical data.

Note: Rails listed are those most commonly used with the 3120/15/40 clip. For compatibility with other rails, inquiries should be made direct to Gantry Railing Limited

GANTRY RAILING LIMITED

International crane rail mounting specialists

NOT FOR DISTRIBUTION IN NORTH AMERICA AND CANADA



GANTRAIL®